



— PRODUCT DATA SHEET

P17



P17

PRODUCT DESCRIPTION

Design and technology have never come together so well. The Ledlenser's P17 casing is black and due its coating has an elegant and velvety appearance. The rippled surface means it sits particularly well in your hand, and what's on the inside also proves that the flashlight has a lot going for it. With a battery life of up to 300 hours¹ on the lowest setting, it continues to shine when other lights have long gone out.

- Optimized operating time – Up to 300 hours¹ in the lowest setting
- Very good lighting performance – Up to 450 meters¹ beam distance with up to 1,000 lumen¹ of luminous flux
- Simple operation – 3 light functions, 1 front switch
- Battery-operated – Three D alkaline batteries (mono, LR20, 1,5 V) are used
- For a long lifetime – Robust metal housing and high-quality gold contacts



TECHNICAL DATA

Length defocused [mm]	312
Length focused [mm]	322
Head diameter [mm]	53
Tube diameter [mm]	40
Weight incl. batteries [g]	785
Weight without batteries [g]	378
Focus function	Yes
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Plastic lense (PMMA)
Cartridge	No

POWER SUPPLY

Power source type	Battery
Battery quantity	3
Battery type	Alkaline
Rechargeable	No
Energy modes	Energy Saving
Usable batteries	D NiMH Pack 4.8V

FURTHER SPECIFICATIONS

IP class	IP54
Drop test (drop height) [m]	1
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Low Power, Power, Boost

LIGHT SOURCE

Amount LEDs	1
LED type	Xtreme LED
Color	White
Color temperature [K]	6000 to 8000
Color rendering index (CRI)	65

LIGHT VALUES

ANSI – Energy Saving	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]	1000	400		100
Beam distance ¹ [m]	450	300		150
Run time ¹ [h]	15	50		300

SWITCH

Front Switch

TECHNOLOGIES

Advanced Focus System³, Rapid Focus

P17

PACKAGING AND LOGISTICS



Exemplary Packaging Illustration



Exemplary Packaging Illustration

PACKAGING INFORMATION

Type of packaging	Gift Box
Scope of delivery	1 set of batteries, Intelligent clip
Item No.	500903
Customs tariff number	85131000
Color	black

SINGLE PACKAGE

Dimensions W x H x D [cm]	36.9 x 6 x 12.4
Gross weight [g]	1185
GTIN-13	4058205009935

EXPORT CARTON

Unit	12
Dimensions W x D x H [cm]	40 x 27.5 x 41.5
Gross weight [kg]	15.2
GTIN-13	4058205010924

PACKAGING INFORMATION

Type of packaging	Blister
Scope of delivery	1 set of batteries, Intelligent clip
Item No.	500904
Customs tariff number	85131000
Color	black

SINGLE PACKAGE

Dimensions W x H x D [cm]	17 x 44 x 5.9
Gross weight [g]	1066
GTIN-13	4058205009942

INNER CARTON

Unit	6
Dimensions W x D x H [cm]	45.5 x 38.5 x 19.5
Gross weight [g]	7491
GTIN-13	4058205010931

EXPORT CARTON

Unit	12
Dimensions W x D x H [cm]	48.5 x 41.5 x 45
Gross weight [kg]	16.3
GTIN-13	4058205010948

P17

ACCESSORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME	MSRP
Color filter / Signal caps	0042	Signal Cone 53mm	
Fastenings / Brackets	500993	Tripod Type A	

P17

PRODUCT SERIES

The Ledlenser P-Series

Minimalist design, maximum performance.

The sturdy flashlights of the Ledlenser P-Series offer top performance in stylish designs. While externally they only have the bare essentials, they are packed full of useful technical functions, like the Rapid Focus and the Advanced Focus System. This makes them dependable companions for all outdoors fans and indispensable little helpers for everyday life: For example, for renovating, tidying and rearranging, taking the dog out, during blackouts, and much more.

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".

3) EP Patent 1880139, US Patent 7,461,960

4) Warranty period of five years from the date of purchase, seven years if the product is registered online on our website. The warranty is valid worldwide and legal warranty rights also apply. It covers defects in materials and workmanship. For the proper functioning of rechargeable batteries a different warranty period of 24 months applies. Excluded from this warranty are the product series "Solidline", Ledlenser K1 and Ledlenser K2. The warranty does not apply to Defects in batteries, holsters, pouches, remote switches, color filters, imprints or surface coatings. The guarantor is Ledlenser GmbH & Co. KG, Kronenstr. 5 - 7, 42699 Solingen, Germany. More information: ledlenser.com/warranty